

PUSH CUTTERS



- The Push Type Cutter can be driven with a Pneumatic or Electric drill motor.
- The tool uses spring-loaded cutters, which are adjustable for depth and cut when pressure is applied during use.
- Two cutter tips as standard on tube sizes from 1".
- The tool has a 6" cutting reach as standard (other lengths available on request).
- Tools listed are 'universal' tools and cover a range of thicknesses with interchangeable pilots.
- Solid body tools, covering a specific tube size, are also available from size 3/8" up (please enquire)

TUBE SIZE (OD.)			PART NUMBER	
mm	INCH	PILOT RANGE	COMPLETE TOOL	CUTTER BIT
15.8	5/8"	16-22g	42.PC-158	42.PCB25186
19.0	3/4"	14-22g	42.PC-190	42.PCB25186
22.2	7.8"	11-22g	42.PC-222	42.PCB25194
25.4	1"	11-13g	42.PC-222	42.PCB25194

Twin Blade Cutters ▼

25.4	1"	14-22g	42.PC-254	42.PCB25199
31.7	1 1/4"	14-22g	42.PC-317	42.PCB25206
38.1	1 1/2"	10-20g	42.PC-381	42.PCB25206
50.8	2"	6-16g	42.PC-508	42.PCB25221
63.5	2 1/2"	8-12g	42.PC-635	42.PCB25223

Tel: +44 (0) 23 8036 6410
Fax: +44 (0) 23 8039 9113

E-mail: tuberunner@bsa-regal.co.uk
Web: www.tuberunner.co.uk